Las Vegas, NV 89118

(800) 293-4698

Product: Penetrating Stone Sealer	Classification: Floor Care			F43				
2 Composition/Information on Hazardous Ingredients								
/laterial	CAS#	%	OSHA(PEL)	TLV(ppm)	Other			
Potassium Methyl Siliconate	31795-24-1	<10	N/A	N/A	N/A			
3 Hazards Identification ergency Overview: May cause skin and eye	e irritation. Avoid s	kin and e	eye contact.					
3 Hazards Identification ergency Overview: May cause skin and eye CAUTION	e irritation. Avoid s	kin and e	eye contact.					
ergency Overview: May cause skin and eye	e irritation. Avoid s	kin and e	ye contact.					

Ingestion Symptoms: Irritation, nausea, vomiting and diarrhea.

Inhalation Symptoms: N/A

Chronic Effects: No data.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

4 First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

- Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult, give oxygen and seek medical attention.
- **Ingestion:** If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute remaining residue. Seek medical attention.

3/6/2006 0001 4010

5 Fire Fighting Measures

Flash Point(F° TCC): >200°F

Flammable Limits: LEL No Data

Auto Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

Local exhaust

Respiratory Protection:

If used according to directions respirator not required.

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

	3/6/2006 0001 4010	Penetrating Stone Sealer Page 2 of 3
--	--------------------	--------------------------------------

9 Physical and Chemical Prop	perties	
Boiling Point(F°)>212°F Specific Gravity:1.02 Appearance:Clear Evaporation Rate:<1	Solubility in WaterSoluble Volatiles(% by Wt.)95 Vapor Density:>1 Vapor Pressure:<17 mm Hg	Odor: Neutral pH: 11.5 - 12.5 VOC: N/A Freezing Point(F°):32°F
	> means less than < means greater that typical values based on material tested but may be construed as a guaranteed analysis of any	y vary from sample to sample.
10 Stability and Reactivity		
Stability: Stable Condition	ions to Avoid: Temp. Extremes	
Materials to Avoid: Strong Oxidize	rs	
Hazardous Decomposition Production Oxides of carbon and nitrogen Hazardous Polymerization:	cts:	
Will Not Occur		
11 Toxicological Information		
No Toxicology Information is available	e.	
12 Ecological Information		
No data available.		
Waste Disposal Method: Dispose of waste in accordance w	ith federal, state and local regulations	
14 Transport Information		
HAZMAT: No Hazard O Hazardous Division:None Hazardous Contents:None	Code: N/A ID Number: N/A	Hazard Class: N/A Packaging Group:N/A
15 Regulatory Information		
Proposition 65: Not Listed. EPA: No 16 Other Information HMIS/NFPA Hazard Rating: Hea	Ith 1 Flammability 0 React	tivity 0
	ased on the data available to us. It is believed t uracy of this data or the results to be obtained Industries, HQ	
3/6/2006 0001 4010		Penetrating Stone Sealer Page 3 of 3