MATERIAL SAFETY DATA SHEET

Fritztile by Expanko, Inc 180 Gordon Drive, Suite 113 Exton, PA 19341

INFORMATION 800.345.6202 610.363.0343 EMERGENCY Call 911

Product Name: FCP102 Date Written: December 15, 1994

<u>Chemical Name</u>: Acrylic Floor Sealer <u>Revision Date</u>: January 29, 2013

Package Quantity: 1 Gal. CAS Number: N/A

<u>Chemical Used</u>: Acrylic Latex Mixture <u>Application</u>: N/A

Health Flammability Reactivity Special

HMIS Rating: 0 0 B

HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Other Limits

Hazardous Components CAS Number OSHA PEL ACGIN TLV Recommended % (optional)

(Specific Chemical Identity; Common Name(s))

DiButyl Phthalate** 84-74-2 5mg/m³ 5mg/m³ <2%

Formaldehyde** 50-00-0 .75ppm 1.2mg/m³ .03%

FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): NE Flammable Limits: NE

Explosive Limits (Lower/Upper): NE Extinguishing Media: Water, foam, dry chemical CO₂

Special Fire Fighting Procedures: None

Unusual Fire and Explosion Hazards: None foreseen

PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor: Amber white liquid, mild acrylic odor.

Specific Gravity (H₂0=1): 1.017 Boiling Point: 212°F

Vapor Pressure (MMHG): NE Melting Point: NA

Vapor Density: >1; Air = 1 Bulk Density: 8.47 lbs/gallon

Solubility In Water: Infinite pH: 8.5

Percent Volatility: 80% Biodegradability: yes

Evaporation Rate: Slower than water Freeze Point: 32°F

Pour Point: 33°F Partition COEF: NE

REACTIVITY DATA

Stability: Unstable: X Conditions To Avoid: None

Incompatibility (Materials To Avoid): None

Hazardous Polymerization: May Occur: Will Not Occur: X Conditions To Avoid: None

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide.

FCP102 Page 1 of 2

HEALTH HAZARD DATA

Route(s) of Entry: Inhalation: Ingestion: Skin: Eyes: X

Signs and Symptoms of Exposure

Inhalation: Ingestion: Skin:

Eyes: Mild eye irritation

Health Hazards (Acute and Chronic): None foreseen

<u>Carcinogenic Determination</u> NTP - No IARC Monographs - No OSHA Regulated - No

Medical Conditions Generally Aggravated by Exposure: None known

Emergency and First Aid Procedures: Rinse eyes and skin contact with water.

PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Pick up with mop, wet vac or hose with water.

Waste Disposal Procedure: Absorb with inert material. Dispose of when dry.

Storage And Handling Conditions: Keep away from excessive heat/direct sunlight.

Precautionary Labeling: Keep from freezing

Container Disposition: Double rinse and recycle plastic containers.

Other Precautions: None

CONTROL MEASURES

Respiratory Protection: None required if good ventilation maintained.

Eye Protection: Splash goggles when filling/transferring liquid.

<u>Hand Protection</u>: None Ventilation: None

Other Protective Equipment: None

ENVIRONMENTAL EVALUATION

EPA Superfund (SARA) Title III - Hazard Classification & Associated Information:

Dibutyl Phthlate,
Formaldehyde.

EPA Cercla/Superfund, 40 CFR 302 (Reportable Spill Quantity): Dibutyl Phthlate, Formaldehyde.

EPA Sara Title III, CFR 355 (Extremely Hazardous Substances): Formaldehyde

EPA Sara Title III, 40 CFR 372 (List of Toxic Chemicals): Dibutyl Phthlate, Formaldehyde

Components Listed On Following Chemical Inventories

TSCA X CEPA EEC ACOIN NPR DRSM

EPA -- RCRA (Hazardous Waste), 40 CRF 261: No

California Proposition 65: No

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Fritztile by Expanko, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

VOC's: 198.6 gms/liter (1.66 lbs./gal)

FCP102 Page 2 of 2